



Key Feature

- Visual Fault Locator is used for locating brokenpoint in fibers .
- Visual Fault Locator is equipped with a 650-nm visible laser diode, can be operated in continuous or pulse modes for clear noticeable results.
- One green LED indicat shows the operating mode.
- Power switch on the end for battery on / off .
- Push button operate CW / Mod. (2.5 Hz frequency) / pause.
- Clip pocket-size pen design.
- Protective cap for extra protection .
- Low Battery Indicator: The Status LED will turn to red when batteries are low.



Product Specifications

Central Wavelength	650 +/- 10 nm	
Output Power	10mW into Single-mode fiber	
Spectral Width	< 8 nm	
Transmission	CW or 2.5 Hz pulse	
Batteries	2 x AAA Alkaline batteries	
Operating Temp.	0 - 50 °C	
Detecion Distance	< 10 Km	WVFL-650-250
	< 6 Km	WVFL-650-125
Dimension / Weight	13.5 mm X 170 mm / 88 g	
Light Source	Class IIIb laser diode	
Suit for	φ2.5 mm Ferrule	WVFL-650-250
	Φ1.25 mm Ferrule	WVFL-650-125

WAVEFORM TECHNOLOGY CO., LTD.

19F., No.258, Sec. 2, Jincheng Rd., Tucheng Dist., New Taipei City 236, Taiwan (R.O.C.)
 E-mail : sales@waveform.com.tw www.waveform.com.tw TEL : +886-2-2260-1657 1-1