



WFT Lab's Optical Fiber Adapters are ultra reliable components featuring low insertion loss and return loss. Optical Fiber Adapter includes FC,SC,ST,LC.MU,MT-RJ with application for Single-mode Fiber and Multi-mode. All plastic material is compatible with the standard of UL 94/V0 grade and customer configurations.

Features

- Easy Installation
- Snap/Latch Mounting Mechanism
- Precision Mechanical dimensions
- Environmentally stable
- Low Insertion Loss and Low Back Reflection Loss
- Compliance with
 FC: IEC 60874-7, JIS C5970-F01
 SC: IEC 60874-04, JIS C5970-F04
 MU: JIS C5983-F14
 ST: IEC 60874-10
 LC: IEC 61754-20

Product Specifications

Application

- CATV/Access Networks
- Data Communications
- Telecommunications
- Component Terminations
- Test Equipment
- FTTH
- LAN

r roduct Specifications			
Specifications		Value	
Item		Single-Mode	Multi-Mode
Connector Type		FC, SC, ST, LC, MU	FC, SC, ST, LC, MU
Sleeve		Ceramic	Bronze
Insertion Loss		0.1dB	0.2dB
Durability (500mating)		≦0 . 15dB	
Retention Force	FC,SC,ST	$200\sim 600$ grams	
	LC,MU	$100{\sim}200$ grams	
Operation Temperature		-40°C ~ 80°C	

WAVEFORM TECHNOLOGY CO., LTD.

19F., No.258, Sec. 2, Jincheng Rd., Tucheng Dist., New Taipei City 236, Taiwan (R.O.C.) *E-mail* : <u>sales@waveform.com.tw</u> <u>www.waveform.com.tw</u> TEL : +886-2-2260-1657 1-1

